

EEPROM DUMP EXPLANATION FILE									
ILLUSTRATES DATA IN THE DUAL CIRCULAR BUFFER									
©2004 RED BYER									
CRIBBAGE BOARD #10: THE WEDDING BOARD									
EXAMPLE :10000000FFFF000102030405060708090A0B0C0D97 EEPROM :100010000E0F10111213141516171819FFFFFFFFFA DATA :10002000FF010001020304000000010203040506B1 DUMP :100030000708090A0B0C0D0E0F1000FFFFFFFFF0150 :00000001FF									
BUFFERSPAN									
1F									
NOTES	EEPROM ADDRESS	DECIMAL EQUIV.	HEX VALUE	DECIMAL EQUIV.	NOTES	EEPROM ADDRESS	DECIMAL EQUIV. MINUS BUFFERSPAN	HEX VALUE	DECIMAL EQUIV.
UNUSED	00	00	FF	255					
POINTER	01	01	FF	255	PCC	20	01	FF	255
BUFFER	02	02	00	00	BUFFER	21	02	01	01
	03	03	01	01		22	03	00	00
	04	04	02	02		23	04	01	01
	05	05	03	03		24	05	02	02
	06	06	04	04		25	06	03	03
	07	07	05	05		26	07	04	04
	08	08	06	06		27	08	00	00
	09	09	07	07		28	09	00	00
	0A	10	08	08		29	10	00	00
	0B	11	09	09		2A	11	01	01
	0C	12	0A	10		2B	12	02	02
	0D	13	0B	11		2C	13	03	03
	0E	14	0C	12		2D	14	04	04
	0F	15	0D	13		2E	15	05	05
	10	16	0E	14		2F	16	06	06
	11	17	0F	15		30	17	07	07
	12	18	10	16		31	18	08	08
	13	19	11	17		32	19	09	09
	14	20	12	18		33	20	0A	10
	15	21	13	19		34	21	0B	11
	16	22	14	20		35	22	0C	12
	17	23	15	21		36	23	0D	13
	18	24	16	22		37	24	0E	14
	19	25	17	23		38	25	0F	15
	1A	26	18	24		39	26	10	16
	1B	27	19	25		3A	27	00	00
	1C	28	FF	255		3B	28	FF	255
	1D	29	FF	255		3C	29	FF	255
	1E	30	FF	255		3D	30	FF	255
	1F	31	FF	255		3E	31	FF	255
				MODEREGADDR		3F		01	01

AFTER SUCCESSFULLY ACCEPTING THE NEW MODE (ADDRESS 0x39) THE PCC WAS PARSED AND THE PROGRAM COUNT (0X0F) SUBTRACTED. THE NEW MODE (0X01) WAS SAVED INTO THE MODEREGADDR (0X3F).